

cod. **552A**

**FASCETTA INOX L=56mm.  
CON GANCIO RAPIDO**

**STAINLESS STEEL BAND L=56mm.  
WITH RAPID HOOK**




Ø





130  
150  
180  
200  
230  
250  
300  
350  
400  
450  
500  
550  
600  
700  
800


**RESISTENZA FASCETTA** BAND RESISTANCE

modalità di rottura <i>breakage methods</i>	forza massima [N] <i>maximum force [N]</i>
cedimento <i>yielding</i>	<b>6218,33</b> (9,81 newton=kg.1)

 **CARATTERISTICHE** \*La fascetta viene realizzata in acciaio inox 304 BA, spessore 0,4mm. (su richiesta spessore 0,5mm.), ha la funzione di collegare e bloccare una coppia di tubi. Il serraggio avviene per mezzo di due staffe inox (brevettate) che saldate agli estremi e tirate per mezzo di una vite e un dado, permettono di stringere la fascetta in modo rapido. \*La fascetta è completa di una vite in acciaio inox TCCE M6 L=40mm. con taglio a cacciavite e un dado M6 11x11 in ottone nichelato.

 **CHARACTERISTICS** \*The band is manufactured in stainless steel 304 BA thickness 0,4mm (thickness 0,5mm on request), it joins and blocks a pair of pipes. Two (patented) stainless steel brackets hold it tight. The brackets are soldered at the ends and tightened with a screw and nut, allowing the band to be pulled tight quickly. \*The bands have a stainless steel screw TCCE M6 L=40mm, with slot cut and a nut M6 11x11 in nickel-plated brass.

 Su richiesta è possibile realizzare ogni tipo di diametro

 All types of diameters are available on request